




EEN NATUURLIJKE BEKRONING.

Glaslijsten/handrailingen, hout


HOUT

EASY GLASS® SYSTEEM - U-profiel, rond




MOD 6925 - Beuken, gelakt

Hout			
INDOOR	Ø		
20.6925.042.40	42,0		L = 2500 mm





MOD 6925 - Eiken, gelakt

Hout			
INDOOR	Ø		
20.6925.042.43	42,0		L = 2500 mm



MOD 6925 - Beuken, P11 gebeitst en gelakt




Hout			
INDOOR	Ø		
20.6925.042.41	42,0		L = 2500 mm



MOD 50 - Ø 42,0 mm

	U	T	
19.5042.208.00	24	8 - 11	L = 2500 mm
19.5042.211.00	24	11,5 - 13,5	L = 2500 mm
19.5042.215.00	24	15	L = 2500 mm
19.5042.216.00	24	16 - 17,5	L = 2500 mm
19.5042.219.00	24	19	L = 2500 mm
19.5042.222.00	24	20 - 21,5	L = 2500 mm
19.5042.008.00	24	8 - 11	L = 5000 mm
19.5042.011.00	24	11,5 - 13,5	L = 5000 mm
19.5042.015.00	24	15	L = 5000 mm
19.5042.016.00	24	16 - 17,5	L = 5000 mm
19.5042.019.00	24	19	L = 5000 mm
19.5042.022.00	24	20 - 21,5	L = 5000 mm
19.5042.508.00	24	8 - 11	L = 25 m
19.5042.511.00	24	11,5 - 13,5	L = 25 m
19.5042.515.00	24	15	L = 25 m
19.5042.516.00	24	16 - 17,5	L = 25 m
19.5042.519.00	24	19	L = 25 m
19.5042.522.00	24	20 - 21,5	L = 25 m

Q-INFO




Q-24
Q-seal, 310 ml
19.1340.310.00



MOD 6729

304			
INDOOR	Ø		
20.6729.042.12	42,0	QS-49 348	2



MOD 6790


304			
INDOOR	Ø		
20.6790.042.12	42,0	QS-49 348	2




MOD 0710

		Q	
19.0710.042.12		Q-20	1


Q-INFO



QS-49 Q-20




Q-21 Q-gluе, 50 ml
19.1331.000.00






**BETAALBARE LUXE.
GEPOLIJSTE U-PROFIEL BUIZEN
KOSTEN MINDER DAN U DENKT!**


**MOD 6920 / 6925**

Ø 42,4 mm

304


INDOOR	Ø	U	H	H1	
13.6925.042.10	42,4	24	37	24	L = 2500 mm
13.6920.042.10	42,4	24	37	24	L = 5000 mm

316


OUTDOOR	Ø	U	H	H1	
14.6925.042.10	42,4	24	37	24	L = 2500 mm
14.6920.042.10	42,4	24	37	24	L = 5000 mm



Ø 48,3 mm

304


INDOOR	Ø	U	H	H1	
13.6925.048.10	48,3	27	42,6	30	L = 2500 mm
13.6920.048.10	48,3	27	42,6	30	L = 5000 mm

316

OUTDOOR	Ø	U	H	H1	
14.6925.048.10	48,3	27	42,6	30	L = 2500 mm
14.6920.048.10	48,3	27	42,6	30	L = 5000 mm

**MOD 50**


Ø 42,4 mm

	U	T	
19.5042.208.00	24	8 - 11	L = 2500 mm
19.5042.211.00	24	11,5 - 13,5	L = 2500 mm
19.5042.215.00	24	15	L = 2500 mm
19.5042.216.00	24	16 - 17,5	L = 2500 mm
19.5042.219.00	24	19	L = 2500 mm
19.5042.222.00	24	20 - 21,5	L = 2500 mm

19.5042.008.00	24	8 - 11	L = 5000 mm
19.5042.011.00	24	11,5 - 13,5	L = 5000 mm
19.5042.015.00	24	15	L = 5000 mm
19.5042.016.00	24	16 - 17,5	L = 5000 mm
19.5042.019.00	24	19	L = 5000 mm
19.5042.022.00	24	20 - 21,5	L = 5000 mm

19.5042.508.00	24	8 - 11	L = 25 m
19.5042.511.00	24	11,5 - 13,5	L = 25 m
19.5042.515.00	24	15	L = 25 m
19.5042.516.00	24	16 - 17,5	L = 25 m
19.5042.519.00	24	19	L = 25 m
19.5042.522.00	24	20 - 21,5	L = 25 m

Ø 48,3 mm

	U	T	
19.5048.008.00	27	8 - 11	L = 5000 mm
19.5048.011.00	27	11,5 - 13,5	L = 5000 mm
19.5048.015.00	27	15 - 17,5	L = 5000 mm
19.5048.019.00	27	19	L = 5000 mm
19.5048.022.00	27	20,5 - 21,5	L = 5000 mm


Q-INFO**MOD 6920**

Berekeningsbasis voor U-profielbuizen

calculated by 


	Ø (mm)	A (cm ²)	I _x (cm ⁴)	I _y (cm ⁴)	W _x (cm ³)	W _y (cm ³)	M (kg/m)	R _{p0,2} (kN/cm ²)	R _m (kN/cm ²)
13.6920.042.10 / 13.6925.042.10	42,4	2,58	2,80	5,11	1,66	2,41	2,02	23	54
14.6920.042.10 / 14.6925.042.10	42,4	2,58	2,80	5,11	1,66	2,41	2,02	24	53
13.6920.048.10 / 13.6925.048.10	48,3	3,02	4,48	7,71	2,33	3,19	2,37	23	54
14.6920.048.10 / 14.6925.048.10	48,3	3,02	4,48	7,71	2,33	3,19	2,37	24	53

A = oppervlakte dwarsdoorsnede W_x / W_y = weerstandsmoment R_{p0,2} = toelaatbare spanning
 I_x / I_y = oppervlaktetraagheidsmoment M = massa R_m = minimale trekvastheid



MOD 6303

304			
INDOOR	Ø	H	
13.6303.042.10	42,4 x 1,5	30	2
13.6303.048.10	48,3 x 1,5	35	2
316			
OUTDOOR	Ø	H	
14.6303.042.10	42,4 x 1,5	30	2
14.6303.048.10	48,3 x 1,5	35	2




MOD 6313

304			
INDOOR	Ø	H	
13.6313.042.10	42,4 x 1,5	30	2
13.6313.048.10	48,3 x 1,5	35	2
316			
OUTDOOR	Ø	H	
14.6313.042.10	42,4 x 1,5	30	2
14.6313.048.10	48,3 x 1,5	35	2



25-55°
Omhoog




MOD 6312

304			
INDOOR	Ø	H	
13.6312.042.10	42,4 x 1,5	30	2
13.6312.048.10	48,3 x 1,5	35	2
316			
OUTDOOR	Ø	H	
14.6312.042.10	42,4 x 1,5	30	2
14.6312.048.10	48,3 x 1,5	35	2



25-55°
Omlaag



MOD 6302

304			
INDOOR	Ø	H	
13.6302.042.10	42,4 x 1,5	30	2
13.6302.048.10	48,3 x 1,5	35	2
316			
OUTDOOR	Ø	H	
14.6302.042.10	42,4 x 1,5	30	2
14.6302.048.10	48,3 x 1,5	35	2



Q-INFO




Q-21
Q-glu
50 ml
19.1331.000.00



Verbruik per verbinding ca. 1 ml

Q-Video www.q-railing.com




MOD 6790

304

INDOOR	Ø	
13.6790.042.10	42,4 x 1,5	2
13.6790.048.10	48,3 x 1,5	2

316

OUTDOOR	Ø	
14.6790.042.10	42,4 x 1,5	2
14.6790.048.10	48,3 x 1,5	2



MOD 6792 - EASY HIT®

304


INDOOR	Ø	
13.6792.042.00	42,4 x 1,5	2
13.6792.048.00	48,3 x 1,5	2

316

OUTDOOR	Ø	
14.6792.042.00	42,4 x 1,5	2
14.6792.048.00	48,3 x 1,5	2



International Design Model Protection




MOD 6505

304

INDOOR	Ø	D	H		
13.6505.042.10	42,4	90	30	QS-5	348 2
13.6505.048.10	48,3	95	35	QS-5	348 2

316

OUTDOOR	Ø	D	H		
14.6505.042.10	42,4	90	30	QS-6	348 2
14.6505.048.10	48,3	95	35	QS-6	348 2



MOD 6732

304

INDOOR	Ø	
13.6732.042.10	42,4 x 1,5	2
13.6732.048.10	48,3 x 1,5	2



316

OUTDOOR	Ø	
14.6732.042.10	42,4 x 1,5	2
14.6732.048.10	48,3 x 1,5	2




Q-INFO

MOD 6792



Q-21
Q-glue
50 ml
19.1331.000.00



Q-INFO



Q-22
Q-ultra-clean
500 ml
19.0610.000.00